

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

PLEASE AMEND THE CLAIMS AS FOLLOW:

1. (Currently Amended) A wireless system for transmitting and receiving a plurality of data packets, the system comprising:

a plurality of directional antenna sectors self contained at a first location, each of the plurality of directional antenna sectors having a respective associated three-dimensional region of space for transmitting and receiving electromagnetic signals;

at least one receiving controller self contained at the first location;

at least one transmitting controller self contained at the first location;

wherein said at least one receiving controller is selectively coupled, one at a time, to each one of the plurality of directional antenna sectors, one at a time, to measure received electromagnetic signal characteristics to determine a best-received electromagnetic signal;

wherein said at least one of said receiving controllers is responsive to the measure of the received electromagnetic signal characteristics from each of the plurality of directional antenna sectors to select one of the directional antenna sectors as a selected directional antenna sector, prior to the transmission of at least one data packet; and

wherein at least one of said transmitting controllers is selectively coupled to the selected directional antenna sector for transmitting said at least one data packet via the selected directional antenna sector.

2. (Original) The system as in Claim 1, wherein a selected one of said at least one receiving controller is selectively coupled to selected ones of the directional antenna sectors in a defined order in order to measure received electromagnetic signal characteristics.

3. (Previously Presented) The system as in Claim 1, wherein prior to the transmission of at least one data packet and responsive to the measure of the received electromagnetic signal characteristics, a selected one of said at least one receiving controller selects at least one of the directional antenna sectors as the selected directional antenna sector within a first defined time interval.

PATENT APPLICATION

Serial Number: 10/814,731

Attorney Docket Number: OFE 1854

4. (Original) The system as in Claim 1, wherein a selected one of said at least one receiving controller selects at least one of the directional antenna sectors within an order dependent upon history of the received electromagnetic signal characteristics prior to the transmission of at least one data packet.

5. (Original) The system as in Claim 1, wherein the plurality of directional antenna sectors are part of at least one of: a mobile device, a laptop computer, a desktop computer, a personal digital assistant (PDA), a cordless phone, a wireless phone, a cellular phone, a 2.5G cellular phone, a 3G device, a 4G device, a 5G device, a multimedia device, a GPS (global positioning system) receiver, an electronic book, electronic paper, an automotive, a boat, a ship, an airplane, a train, a satellite, a hand-held device, a base station, an access point, an access router, a UAV (unmanned aerial vehicle), and a packet switch output.

6. (Original) The system as in Claim 1, wherein the receiving controller is part of at least one of: a mobile device, a laptop computer, a personal digital assistant, a cordless phone, a wireless phone, voice-over IP, a RFID (radio frequency identifier), a cellular phone, a 2.5G cellular phone, a 3G device, a 4G device, a 5G device, a multimedia device, a GPS (global positioning system) receiver, an electronic book, electronic paper, and a packet switch.

7. (Original) The system as in Claim 1, wherein at least one of the plurality of directional antenna sectors are polarized antennas, and
wherein each said polarized antenna sector transmits an electromagnetic signal in a defined polarization.

8. (Original) The system as in Claim 1, wherein each said directional antenna sector transmits in a defined direction that is defined by physical construction of the respective directional antenna sector.

9. (Original) The system as in Claim 8, wherein each said directional antenna sector is

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

associated with a respective transmission region in three-dimensional space; and

wherein the respective transmission regions in three-dimensional space are overlapped within defined parts of three-dimensional space.

10. (Original) The system as in Claim 9, wherein the respective transmission regions in three-dimensional space are defined with accordance to 3db power lobes.

11. (Original) The system as in Claim 1, wherein selected ones of the directional antenna sectors are steered antennas, wherein the steered antennas receive and transmit electro-magnetic signals within a defined region in at least one of: two-dimensional space and three-dimensional space.

12. (Original) The system as in Claim 11, wherein the steered antenna sectors are moveable by at least one of: a step-motor, an electric motor, an electric field, a magnetic field, and a phase array.

13. (Original) The system as in Claim 1, wherein the directional antenna sectors are arranged in a predefined pattern; and

wherein the predefined pattern is at least one of: polyhedron, polygon, octahedron, pentagon, cube, pyramid, sectorized cylinder, ball, pentagondodecahedron, and icositetrahedron.

14. (Original) The system as in Claim 1, wherein there is a plurality of receiving controllers, the system further comprising:

a receiving switch; and

wherein selected ones of the receiving controllers are selectively coupled to selected ones of the directional antenna sectors utilizing the receiving switch.

15. (Original) The system as in Claim 14, wherein the receiving switch is constructed by utilizing high impedance amplifiers.

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

16. (Original) The system as in Claim 14, further comprising:
a plurality of receiver radio frequencies devices (RRFs);
wherein the receiving switch has N inputs and R outputs;
wherein the N inputs are selectively connected to the directional antenna sectors; and
wherein the R outputs are selectively connected to selected ones of the plurality of the RRFs.
17. (Original) The system as in Claim 1, wherein there are a plurality of receiving controllers, and wherein there are a plurality of the transmitting controllers, the system further comprising:
an RF switch,
wherein selected ones of the receiving controllers are selectively coupled to selected ones of the directional antenna sectors utilizing the RF (radio frequency) switch; and
wherein selected ones of the transmitting controllers are selectively coupled to at least one of the directional antenna sectors utilizing the RF switch.
18. (Original) The system as in Claim 1, wherein there is a plurality of the transmitting controllers, the system further comprising:
a transmitting switch; and
wherein selected ones of the transmitting controllers are selectively coupled to at least one of the directional antenna sectors utilizing the transmitting switch.
19. (Original) The system as in Claim 18, wherein the transmitting switch is comprised of high impedance amplifiers.
20. (Original) The system as in Claim 18, further comprising:

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

a plurality of transmitter radio frequencies devices (TRFs);
wherein the transmitting switch has T inputs and N outputs;
wherein the N outputs are selectively connected to the directional antenna sectors, and
wherein the T inputs are connected to selected ones of the plurality of the TRFs.

21. (Original) The system as in Claim 1, wherein there are a plurality of the receiving controllers, and

wherein each of the plurality of the receiving controllers is selectively coupled to selected ones of the directional antenna sectors in at least one of: a random order and a defined order for providing for measurement of the received electromagnetic signal characteristics.

22. (Original) The system as in Claim 1, wherein there are a plurality of the receiving controllers, and

wherein selected ones of the receiving controllers are selectively coupled to selected ones of the directional antenna sectors in at least one of the following patterns: reoccurring, one at a time, two at a time, three at a time, bisection, opposite directions, intersecting sets.

23. (Original) The system as in Claim 1, wherein the received electromagnetic signal characteristics are provided as signals comprising control information and data information.

24. (Original) The system as in Claim 23, wherein the control information is representative of at least one of: RSSI (received signal strength indicator), power, polarization, SNR (signal-to-noise-ratio), Doppler shift, packet source identification, transmitting identification, base station identification, access point identification, bit error-rate, phase-shift, wherein the control information is processed to determine the received electro-magnetic characteristics.

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

25. (Original) The system as in Claim 23, wherein the received electromagnetic signal characteristics are determined by at least one of the following: RSSI (received signal strength indicator) analysis, analog processing, digital processing, analog filtering, digital filtering, FEC (forward error correction), bit error-rate analysis, time-of-day analysis, propagation delay analysis, transmitter address analysis, and transmitter identification analysis.

26. (Original) The system as in Claim 23, wherein the control information is used by a selected one of the receiving controllers to select at least one of the plurality of directional antenna sectors.

27. (Previously Presented) The system as in Claim 23, further comprising:
an antenna control unit; and
wherein the control information is used by the antenna control unit to select at least one of the plurality of directional antenna sectors.

28. (Original) The system as in Claim 1, wherein the directional antenna sectors are physically arranged into a shape having a plurality of facets, wherein each directional antenna sector transmits electromagnetic signals in a defined direction in three-dimensional space, and
wherein the defined direction in three-dimensional space is at least one of:
perpendicular to a polyhedron facet, perpendicular to a pyramid facet, perpendicular to a cube facet, a predefined angle with respect to a polyhedron facet, a predefined angle with respect to a pyramid facet, a predefined angle with respect to a cube facet, a predefined angle with respect to a octahedron facet, and a predefined angle with respect to a pentagondonecahedron facet.

29. (Previously Presented) The system as in Claim 23, further comprising:
means for detecting an identification source of the received electromagnetic signal responsive to the control information;
wherein there is a plurality of the receiving controllers;
wherein a selected one of the receiving controllers selects at least one of

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

the directional antenna sectors prior to transmission of at least one data packet and responsive to the received electromagnetic signal characteristics and the identification of the source of the best-received electromagnetic signal;
wherein there are a plurality of the transmitting controllers; and
wherein a selected one of the transmitting controllers is selectively coupled to at least one of the directional antenna sectors to transmit at least one data packet as selected by the selected one of the receiving controllers.

30. (Original) The system as in Claim 29, wherein the identification source is at least one of: a wireless access point, a base station, a cellular phone base station, a mobile device, an 802.11 device, an 802.15 device, an 802.16 device, a laptop computer, a desktop computer, a personal digital assistance, and a cellular phone.

31. (Previously Presented) The system as in Claim 52,
wherein the at least one of said transmitting controllers is selectively coupled to at least one of the directional antenna sectors for a first defined time interval for the transmission of at least one data packet responsive to the received electromagnetic signal characteristics stored in the first buffer.

32. (Original) The system as in Claim 31, wherein at least one of the at least one said receiving controller is coupled to at least one of the directional antenna sectors for a second defined time interval for receiving of at least one data packet, responsive to the received electromagnetic signal characteristics stored in the first buffer.

33. (Previously Presented) The system as in Claim 52, wherein the at least one said receiving controller is selectively coupled to the directional antenna sectors in a defined order responsive to the electromagnetic signal characteristics stored in the first buffer.

34. (Previously Presented) The system as in Claim 52, wherein the at least one said receiving controller is selectively coupled to the directional antenna sectors in at least one of the following

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

patterns, responsive to the electromagnetic signal characteristics stored in the first buffer as at least: one directional antenna sector at a time, two directional antenna sectors at a time, three directional antenna sectors at a time.

35. (Previously Presented) The system as in Claim 52, further comprising:
- a wireless device contains at least one of: the plurality of antenna sectors, the receiving controller; the transmitting controller and the first buffer; and
 - an antenna system comprises at least one of: the plurality of directional antenna sectors, the at least one said receiving controller; the at least one said transmitting controller and the first buffer.

36. (Original) The system as in Claim 35, wherein the wireless device and the antenna system are coupled to each other by at least one of the following: a plurality of coax cables, a multi-lead coax cable, a parallel data connection, serial data connection, a parallel data and control connection, a parallel data, a timing and control connection, a PCMCIA (personal computer memory card international association) interface, a USB (universal serial bus) interface, an IEEE 1394 (Fire-Wire) interface, an infra red (IR) interface, a free space optical laser interface, and a wireless interface.

37. (Original) The system as in Claim 35, further comprising:
- an access control unit for managing the transmitting and receiving of the data packets, and
 - wherein the access control unit is part of at least one of: the wireless device and the antenna system.

38. (Original) The system as in Claim 35, further comprising:
- an antenna control unit for managing selection of the directional antenna sectors;
 - wherein the antenna control unit is part of at least one of: the wireless device and the antenna system; and
 - wherein the antenna control unit processes the received electromagnetic

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

signal characteristics stored in the first buffer to select at least one of the directional antenna sectors for the first predefined time interval for transmission of data packets.

39. (Original) The system as in Claim 38, wherein the antenna control unit performs parts of at least one of the following protocols: IEEE 802.11, IEEE 802.15, IEEE 802.16, CDMA 2000, WCDMA, UMTS, GPRS, 2.5G, 3G, 4G, 5G, and GSM.

40. (Original) The system as in Claim 35, wherein the wireless device is part of at least one of the following: a laptop computer, a personal computer, a personal digital assistant, a cellular phone, a 2.5G cellular phone, a 3G device, a 4G device, a consumer electronic game, a multimedia device, a videoconferencing system, a wireless packet audio system, a wireless packet video system, an electronic book, a home entertainment system, electronic paper, a GPS (global positioning system) receiver, an automotive, a boat, a ship, an airplane, a trains, a satellite, a hand-held device, a base stations, a wireless access point, an access router, an electronic scanner, a UAV (unmanned aerial vehicle), and a packet switch.

41. (Previously Presented) The system as in Claim 52, further comprising:
at least one omni antenna, and
wherein the at least one said omni antenna is coupled to at least one of the following: said at least one said receiving controller and said at least one said transmitting controller.

42. (Previously Presented) The system as in Claim 52, wherein each of the directional sector antennas is selected from at least one of the following types: flat panel, parabolic dish, slotted, micro-strip, yagi, omni, and planar.

43. (Currently Amended) A wireless method for transmitting and receiving a plurality of data packets, the method comprising:
providing a plurality of directional antenna sectors in three-dimensional space

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

self contained at a first location;

selecting as selected directional antenna sectors, at least one of said plurality of directional antenna sectors, for receiving of an electromagnetic signal;

coupling each one of said selected directional antenna sectors, one at a time, for measuring electromagnetic signal characteristics of the electromagnetic signal at the first location; and

selecting at least one of said plurality of directional antenna sectors as a selected directional antenna sector, to transmit at the first location an electromagnetic signal comprising at least one data packet responsive to the measuring the received electromagnetic signal characteristics to determine a best-received electromagnetic signal.

44. (Original) The method as in Claim 43, further comprising:
utilizing steered directional antenna sectors to orient the directional antenna sectors.
45. (Original) The method as in Claim 43, further comprising:
arranging the directional antenna sectors in a defined physical pattern.
46. (Original) The method as in Claim 43, further utilizing:
converting the received electromagnetic signal to provide control information and data information.
47. (Original) The method as in Claim 46, wherein the control information is representative of at least one of the following: power, polarization, SNR (signal-to-noise-ratio), Doppler shift, phase shift, packet source identification, transmitting identification, base station identification, access point identification.
48. (Original) The method as in Claim 46, further comprising:
determining the electromagnetic signal characteristics by at least one of the

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

following: analog processing, digital processing, analog filtering, digital filtering, FEC (forward error correction), bit error rate analysis, RSSI (received signal strength indicator) analysis, timing analysis, time-of-day analysis, propagation delay analysis, transmitter address analysis, communications channel analysis and transmitter identification analysis.

49. (Original) The method as in Claim 43, further comprising:
communicating the electromagnetic signal via a plurality of channels.
50. (Original) The method as in Claim 49, further comprising:
selecting at least one of the plurality of channels responsive to defined performance selection criteria.
51. (Original) The method as in Claim 50, wherein the defined performance selection criteria is at least one of the following: analog processing, digital processing, analog filtering, digital filtering, FEC (forward error correction), bit error rate analysis, RSSI (received signal strength indicator) analysis, timing analysis, time-of-day analysis, propagation delay analysis, transmitter address analysis, communications channel analysis and transmitter identification analysis.
52. (Original) The system as in Claim 1, wherein the received electromagnetic signal characteristics are stored in a first buffer providing memory for storage; and
wherein the receiving controller selects responsive to the received electromagnetic signal characteristics as stored in the first buffer.
53. (Original) The method as in Claim 43, further comprising: transmitting the electromagnetic signal as a transmitted signal in a defined region in space prior to transmitting of at least one data packet responsive to the electromagnetic signal characteristics.
54. (Currently Amended) A method for transmitting and receiving a plurality of data packets, the method comprising:

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

receiving and measuring, self contained at a first location, electromagnetic signals via a plurality of directional antenna sectors self contained ~~located at a~~ the first location, each of said directional antenna sectors having a respective associated three-dimensional region of space;

determining, at the first location, of received electromagnetic signal characteristics responsive to the measuring at each one of the directional antenna sectors to determine a best-received electromagnetic signal;

selecting at least one of the directional antenna sectors as a selected directional antenna sector, responsive to the determining of the best-received electromagnetic signal; and

transmitting, at the first location, at least one data packet via the selected directional antenna sector.

55. (Previously Presented) The method as in Claim 54, wherein the determining of the best-received electromagnetic signal is determined by at least one of the following: RSSI (received signal strength indicator) analysis, analog processing, digital processing, analog filtering, digital filtering, FEC (forward error correction), bit error-rate analysis, time-of-day analysis, propagation delay analysis, transmitter address analysis, and transmitter identification analysis.

56. (Original) The method as in Claim 54, further comprising:

physically arranging the directional antenna sectors into a shape having a plurality of facets, wherein each of the directional antenna sectors transmit electromagnetic signals in a defined direction in three-dimensional space, and

wherein the defined direction in three-dimensional space is at least one of: perpendicular to a polyhedron facet, perpendicular to a pyramid facet, perpendicular to a cube facet, a predefined angle with respect to a polyhedron facet, a predefined angle with respect to a pyramid facet, a predefined angle with respect to a cube facet, a predefined angle with respect to a octahedron facet, and a predefined angle with respect to a pentagondonecahedron facet.

PATENT APPLICATION
Serial Number: 10/814,731
Attorney Docket Number: OFE 1854

57. (Previously Presented) The method as in Claim 54, further comprising:
- detecting an identification source of the received electromagnetic signal responsive to control information;
 - selecting at least one of the directional antenna sectors as a selected directional antenna sector, prior to transmission of at least one data packet and responsive to the determining of the best-received electromagnetic signal and the identification of the source of the received electromagnetic signal; and
 - selectively coupling the selected directional antenna sectors to transmit at least one data packet.